

SECTION XX. TECHNOLOGIES ET SYSTÈMES D'INFORMATION

DOI 10.36074/logos-08.07.2022.049

DEVELOPMENT OF AN ALGORITHM FOR ESP32-CAM OPERATION IN HTTP SERVER MODE FOR STREAMING VIDEO

ORCID ID: 0000-0002-2590-7085

Yevsieiev Vladyslav

Doctor of Engineering Science, Professor,
Department of Computer-Integrated Technologies, Automation and Mechatronics
Kharkiv National University of Radio Electronics

ORCID ID: 0000-0002-1375-9337

Svitlana Maksymova

Candidate of Engineering Science, Associate Professor,
Department of Computer-Integrated Technologies, Automation and Mechatronics
Kharkiv National University of Radio Electronics

ORCID ID: 0000-0001-7856-5771

Nikolaj Starodubcev

Candidate of Engineering Science, Associate Professor,
Department of Computer-Integrated Technologies, Automation and Mechatronics
Kharkiv National University of Radio Electronics

UKRAINE

One of the key factors in mobile robots development is the choice and implementation of the control system [1]. Analyzing publications on the development of portable or small-sized mobile robots for solving specialized or point tasks, it was found that many authors use the concept of the Internet of Things (IoT) to implement a control system and computer vision [2]. The works of Azis Isrofi, Shoffin Nahwa Utama and Rishabh Chauhan show a mobile robot control system implementation example based on ESP32-Cam [3,4]. Unfortunately, the authors use an external mobile device with the function of creating a Wi-Fi point to control a mobile robot, which is not always acceptable. The authors LIM, Myung-Jae and Lalu Fatwa Aulia in their research analyze IoT technology algorithms for implementing work with miniature mobile robots [5,6]. But the authors do not show how they implement the control system and operator connection. Based on the analysis carried out in this research, an algorithm for dynamic connection to a mobile robot control system based on ESP32-CAM was developed, it is shown in Figure 1.

A feature of the developed algorithm is the flexibility of connection and independence from the device type, one of the important criteria is the support of a Wi-Fi connection and the presence of any Web browser.

The algorithm for connecting / creating an HTTP server involves the following main stages of the program. It should be noted that this algorithm is inside the void setup () procedure. Therefore, after successfully activating the port connection, the installed camera configurations are launched. The next step is to search for a Wi-Fi point according to the SSID specified in the constant inside the program, if a network with this name is found, it is validated by checking the access password.




Fig. 1. Enlarged Algorithm for Connecting/Creating of an HTTP server based on ESP32-CAM

If the validation is successful, the ESP32-CAM module receives registration in the network in the form of a dynamic IP address, which is displayed to the operator in the port monitor. If it is not possible to connect to the specified point, it is proposed to create and implement the ESP32-CAM module as an access point with the possibility of remote connection to it, for this the operator must connect to the access point with a specialized SSID and enter a password known only to unauthorized access. Upon successful connection / creation of a Wi-Fi point, the algorithm stops working and initializes the HTTP server to implement the control system.

Conclusions: The developed enlarged algorithm for connecting / creating an HTTP server based on ESP32-CAM will allow to develop flexible mechanisms for connecting a control system, depending on the need, and will also ensure reliable connection using authentication functions.

References:

- [1] Saenz, A., Santibañez, V., Bugarin, E. et al. (2021). Velocity Control of an Omnidirectional Wheeled Mobile Robot Using Computed Voltage Control with Visual Feedback: Experimental Results. *Int. J. Control Autom. Syst.* 19, 1089–1102 <https://doi.org/10.1007/s12555-019-1057-6>
- [2] Jingjing Wang. (2021). Research on Data Fusion Technology of Mobile Intelligent Robot Based on Internet of Things. *IOP Conf. Series: Earth and Environmental, Science* 707, DOI:10.1088/1755-1315/707/1/012007
- [3] Azis Isrofi, Shoffin Nahwa Utama, Oddy Virgantara Putra. (2021). Rancang Bangun Robot Pemotong Rumput Otomatis Menggunakan Wireleskontroler Modul ESP32-Cam Berbasis Internet Of Things (IoT). *Jurnal TeknoInfo*, Vol. 15, No. 1, P. 45-55. DOI : 10.33365/jti.v15i1.675
- [4] Rishabh Chauhan; S. Bandopadhaya; Mayank Dev; A. Mishra; Lalat Indu Giri; Biplap Kharel; Soumya Ranjan Samal. (2021). Design of Robotic Snake with ESP 32 CAM and Arduino. *In 19th OITS International Conference on Information Technology (OCIT)*. 16-18 December. Bhubaneswar, India. DOI: 10.1109/OCIT53463.2021.00013
- [5] LIM, Myung-Jae, KWON, Young-Man. (2021). An Image Analysis system Design using Arduino sensor and feature point extraction algorithm to prevent to prevent intrusion. *Korea Journal of Artificial Intelligence (한국인공지능학회지)*, Volume 9, Issue 2, Pages. 23-28. DOI: 10.24225/kjai.2021.9.2.23
- [6] Lalu Muhammad Fatwa Aulia, Suryo Adi Wibowo, Nurlaily Vendyansyah. (2021). Penerapan IoT Pada Rancang Bangun Sistem Miniatur Robot Pemadam API Untuk Membantu Proses Evaluasi Pra Evakuasi. *Jurnal Mahasiswa Teknik Informatika*. Vol. 5, No. 1. DOI: <https://doi.org/10.36040/jati.v5i1.3307>